



ANALYTIC SYSTEMS

Power Conversion Solutions

AC/AC Frequency
Converters

Model
FTP6000R



Description

The FTP6000R AC/AC frequency converter provides 3-phase power from a single-phase line outlet. The standard unit delivers 3-phase outputs of 208rms, 380Vrms or 415Vrms continuous at 50, 60, or 400Hz.

The floating outputs are isolated from each other and can be connected in a 'Y' configuration or left as three individual outputs. In 'Y' configuration, the centre point (neutral) can be grounded.

The FTP6000R can be shut down electronically via a control switch on the front-panel of the unit.

Remote shut-down and output voltage adjustment options are available. The unit features full electronic protection, high efficiency and low input and output noise.

Benefits

- ◆ Ultra-Quiet
- ◆ Power sensitive electronics without interference
- ◆ Rugged & Reliable
- ◆ Ensure years of safe and trouble free operation

Design Features

- ◆ Sinusoidal wave shape
- ◆ Isolated, floating output
- ◆ 6000VA output power
- ◆ Full electronic protection
- ◆ Telecom quality
- ◆ Field-proven design topology

Applications

- ◆ Aviation / Marine
- ◆ Electric Utilities and Substations
- ◆ Telecom Power Plants
- ◆ Manufacturing Locations
- ◆ Steel Mills
- ◆ Military Applications (COTS)
- ◆ Industrial Controls
- ◆ OEM Applications
- ◆ Solar / Alternative Power Systems
- ◆ Fuel Cells

AC/AC Frequency Converters

FTP6000R

Input Voltage	115VAC, 60Hz - 400Hz or 230VAC, 50Hz single phase Other inputs available, please consult factory
Input Protection	Thermal fuse, Inrush current limiting
Isolation	2250 VDC input to chassis / 2250 VDC input to output / 2250 VDC output to chassis
Output Voltages	208rms/ 3-phase continuous or 380Vrms/3-phase continuous or 415Vrms/3-phase continuous at 50, 60, or 400Hz The centre point (neutral) is floating - it can be grounded Consult factory for other voltages and frequencies
Wave Form	Sinusoidal
Total Harmonic Distortion	Less than 5% at full load
Efficiency	Min 78% at full load
Line Regulation	Maximum 0.5%
Load Regulation	Maximum \pm 6% from 10% load to full load
Output Protection	Current limiting with short circuit protection, thermal shutdown with automatic recovery in case of continuous overload or insufficient airflow
EMI	EN 55022 Class B (typical)
Load Crest Factor	Maximum 3.0 at 90% load
Frequency Stability	\pm 0.1%
Operating Temperature Range	0o C to +50o C (Extended range available, Consult factory)
Humidity	5 - 95% non-condensing
Temperature Drift	0.05% per o C over operating temperature range
Dimensions	12U x 19" x 15" Rack Mount Enclosure Depth: 17" maximum
Connections	Input/output: terminal block
Weight	90 pounds (40kg)
Safety	Designed to meet C22.2 No. 107.1 - 01, UL 458 and EN60950 Please contact factory for approval status for the requested input/output configuration

Warranty: Twenty Four months subject to application within good engineering practice. Enhancements to these general specifications can be accommodated upon request
Designed to meet common approval requirements. Specifications Subject to Change Without Notice. Designed and Manufactured in Canada



ANALYTIC SYSTEMS
Power Conversion Solutions

8128 River Way, Delta B.C. V4G 1K5 Canada T. 604.946.9981 F. 604.946.9983 TF. 1.800.668.3884 (US/CANADA)

www.analyticsystems.com