

# 150VA Sine Wave Inverter for Railway Applications

## RSI 150-FT Series



- Field-proven rugged design
- Conduction/convection cooled - no fan
- Low profile, compact size
- Sinusoidal wave shape
- Full electronic protection

This rugged DC/AC inverter uses field proven, microprocessor controlled high frequency PWM technology to generate the required output power with pure sine wave output voltage. It is a mature design with a track record in numerous applications. The DC/DC input stage boosts the input voltage to a higher DC voltage, which feeds the DC/AC inverter to generate the required AC output. The high frequency conversion enables a compact construction, low weight and high efficiency. The unit has full electronic protection. The input and output are filtered for low noise. Cooling is via baseplate to a cold plate surface and by additional natural convection. The use of components with established reliability results in high MTBF. The unit meets the requirements of EN 50155 for electronic equipment used on railway rolling stock. It is manufactured at our plant under strict quality control. Customized versions are available.

### SPECIFICATIONS

#### Input Voltage

24Vdc (17 – 34V)  
 36Vdc (25 – 51V)  
 48Vdc (33 – 67V)  
 72Vdc (50 – 101V)  
 96Vdc (67 – 135V)  
 110Vdc (77 – 154V)  
 Consult factory for other input voltages and ranges

#### Input Protection

Inrush current limiting  
 Varistor  
 Reverse polarity protection  
 Internal safety fuse  
 Lower voltage than the specified minimum input will not damage the unit

#### Isolation

1500Vdc input to chassis  
 3000Vdc input to output

#### Standards

Designed to meet  
 C22.2 No. 107.1 - 01, UL 458,  
 EN60950 and EN50155

#### Immunity

Meets criteria of EN50155 and EN50121-3-2 including  
 EN 61000-4-2 (ESD)  
 EN61000-4-3 (RF Immunity)  
 EN61000-4-4 (Fast transients)  
 EN50155 (Surge)  
 EN61000-4-6 (Conducted Imm.)  
 EN50155 (Voltage Variations)

#### EMI

EN55022 Class A or B according to requirements, and  
 EN50121-3-2 conducted and radiated

#### Output Voltage

115Vac @60Hz or 400Hz/1.3Arms continuous; or  
 230Vac @ 50Hz/0.65Arms continuous  
 Isolated floating output  
 Consult factory for other output requirements

#### Output Wave Form

Sinusoidal

#### Total Harmonic Distortion

Less than 5% at full load

#### Line Regulation

Maximum 0.5%

#### Load Regulation

Maximum  $\pm 2\%$  from no load to full load.

#### Load Crest Factor

Maximum 3.0 at 90% load

#### Output Noise

High frequency ripple is less than 500mVrms (20MHz BW)

#### Output Overload Protection

Current limiting with short circuit protection  
 Thermal shutdown with automatic recovery in case of insufficient cooling

#### Output Overvoltage Protection

140Vac (for 115Vac output) or 280Vac (for 230Vac output) by internal supply voltage limiting

#### Efficiency

Typically 80% at full load  
 Dependent on input/output combination

#### Operating Temperature

-25 to +50°C cold-plate temperature for full specification

#### Temperature Drift

0.05% per °C over operating temperature range

#### Cooling

Conduction to customer heat-sink or chassis and natural convection

#### Environmental Protection

Ruggedizing  
 Conformal coating

#### Shock/Vibration

IEC 61373 Cat 1 A&B

#### Humidity

5 - 95% non-condensing

#### MTBF

150,000 hours at 45 °C  
 Demonstrated MTBF is significantly higher

#### Indicators

None

#### Control Input

None

#### Alarm Output

None  
 Optional output Fail Alarm (Form C)

#### Dimensions

F2: 114 x 58 x 256 mm  
 (4.5" x 2.3" x 10.1") including terminal block and flanges  
 Mounting holes are clear

#### Weight

Approx. 1.2 kg (2.6 lb.)

#### Connections

Barrier-type terminal block with 3/8" spacing

#### RoHS Compliance

Fully compliant

#### Warranty

Two years subject to application within good engineering practice

#### Terminal Block Pin-Out

AC OUTPUT			ALARM (OPTION)			DC INPUT		
NOT USED	L1	L2	FAIL OPEN	COM	FAIL CLOSED	GND	+	-
1	2	3	4	5	6	7	8	9

Please note that ABSOPULSE inverters are designed and built to customer specifications. The specifications on this data sheet are generic and will vary depending on input/output configuration and other customer requirements. Generic specifications are subject to change.

*Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility*



#### ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario. K0A 1L0. CANADA

Tel: +1-613-836-3511 | Fax: +1-613-836-7488

E-mail: [absopulse@absopulse.com](mailto:absopulse@absopulse.com) | <http://www.absopulse.com>

For more information, please see:

[http://www.absopulse.com/Absopulse\\_railway\\_mobile\\_extreme\\_environment\\_solutions.php](http://www.absopulse.com/Absopulse_railway_mobile_extreme_environment_solutions.php)

November 7, 2012/TS/OP/CL

Made in Canada